

COMELZ-ISRAEL

24 YOM HA'KIPURIM ST. HOLON 58485 ISRAEL
TL: +972-505256468 FAX : +972-3-5566824
www.a-saranga.com comelz.israel@gmail.com



א.ס. שרותי הנדסה

רח' יום הכיפורים 24 חולון 5848567
טל. 03-558172 6 פקס 03-5566824
אבי סרנגה נייד. 050-5256468

מכונת פיצול

CAMOGA C520

Camoga
COMELZ_GROUP


Divide/Line C520 splitters are designed and manufactured accordingly to the main principles of Camoga products:

QUALITY of materials and of manufactured components allow to achieve and keep high performances for a long time.

SIMPLICITY of use and maintenance to limit the unproductive stops and the operation expenses.

Therefore they are very **RELIABLE AND FLEXIBLE** machines, because without restriction of quality, they allow high productivity with a perfect adaptation for the different working methods and the different features of all kind of materials.

The wide range of models available meet all requirements, from the small firm to the big industry.



Features



- No knife trend setting ••
- Grinding unit suitable for corundum or diamond wheels ••
 - easy: single micrometric control ••
 - flexible: fast setting of bevel width ••
- Guide gibs group with automatic adjustment
- Independent exhausters for emery dust and working scraps
- Moving wheel moving on precision roller guides ••
- Working pressure fast adjustment ••
- Optical viewer to check bevel symmetry
- Digital thickness readout ••
- Handbook and service tools
- Ergonomic work position to reduce tiredness ••
- Safety devices compliance with CE standards
- Low noise level
- Fast replacement Guide Roll/Guide Bar without removing joint ••
- Access to all components for an easy and rapid maintenance
- Life lubricated mechanical components
- Features introduced by Camoga for the first time

Accessories

Upper Feed Roll N (8/0.6 mm)
 Special Up Feed Roll S
 Rubber Coated Bot Feed Roll
 Alternative grinding unit: Diam/Corum
 Mechanical Thickness Gauge
 Special low friction feed tables

Equipments

Equipment to skive edges of the straps
 Equipment to skive tip, edges and back of the belts
 Remover unit for split pieces

Model

	C 520 R	C 520 L
Feeding Speed	4 Ele-Mec	Vario
Upper Feeding	Standard	Standard
Toe-Split	No	Standard
Working Pressure	Mechanical	Mechanical
Alarms	Touch screen	Touch screen
Instr. & Messages	Touch screen	Touch screen
Installed Power	3.4 kW	3.6 kW
Net Weight	670 kg	685 kg
Gross Weight	871 kg	886 kg
Mc. Dimensions (m)	1.7x1.1x1.3	1.7x1.1x1.3
Case Dimensions (m)	1.85x1.2x1.45	1.85x1.2x1.45

Technical Data

Working Width	520 mm
Max Thickness	8 mm
Min Thickness	0.6/0.2 mm
Knife Dimension	0.8*50*3700 mm