

**COMELZ-ISRAEL**

24 YOM HA'KIPURIM ST. HOLON 58485 ISRAEL  
TL: +972-505256468 FAX : +972-3-5566824  
[www.a-saranga.com](http://www.a-saranga.com) [comelz.israel@gmail.com](mailto:comelz.israel@gmail.com)



**א.ס. שרותי הנדסה**

רח' יום הכיפורים 24 חולון 5848567  
טל. 03-558172 6 פקס 03-5566824  
אבי סרנגה נייד. 050-5256468

**מכונת פיצול**

**CAMOGA C420**

**Camoga**  
**COMELZ\_GROUP**


Divide/Line C420 splitters are designed and manufactured accordingly to the main principles of Camoga products:

**QUALITY** of materials and of manufactured components allow to achieve and keep high performances for a long time.

**SIMPLICITY** of use and maintenance to limit the unproductive stops and the operation expenses.

Therefore they are very **RELIABLE AND FLEXIBLE** machines, because without restriction of quality, they allow high productivity with a perfect adaptation for the different working methods and the different features of all kind of materials.

The wide range of models available meet all requirements, from the small firm to the big industry.



## Features

- No knife trend setting ••
- Grinding unit suitable for corundum or diamond wheels ••
  - easy: single micrometric control ••
  - flexible: fast setting of bevel width ••
- Guide gibs group with automatic adjustment
- Independent exhausters for emery dust and working scraps
- Moving wheel on precision roller guides ••
- Working pressure fast adjustment ••
- Optical viewer to check bevel symmetry
- Digital thickness readout ••
- Handbook and service tools
- Ergonomic work position to reduce tiredness ••
- Safety devices compliance with CE standards
- Low noise level
- Fast replacement Guide Roll/Guide Bar without removing joint ••
- Access to all components for an easy and rapid maintenance
- Life lubricated mechanical components
- Features introduced by Camoga for the first time



## Accessories

Upper Feed Roll N (8/0.6 mm)  
 Special Up Feed Roll S  
 Rubber Coated Bot Feed Roll  
 Alternative grinding unit: Diam/Corum  
 Mechanical Thickness Gauge  
 Special low friction feed tables

## Equipments

Equipment to skive edges of the straps  
 Equipment to skive tip, edges and back of the belts  
 Remover unit for split pieces

## Model

	C 420 R	C 420 L
Feeding Speed	4 Ele-Mec	Vario
Upper Feeding	Standard	Standard
Toe-Split	No	Standard
Working Pressure	Mechanical	Mechanical
Alarms	Touch screen	Touch screen
Instr. & Messages	Touch screen	Touch screen
Installed Power	3.0 kW	3.2 kW
Net Weight	600 kg	600 kg
Gross Weight	782 kg	782 kg
Mc. Dimensions (m)	1.6x1.1x1.25	1.6x1.1x1.25
Case Dimensions (m)	1.75x1.2x1.45	1.75x1.2x1.45

## Technical Data

Working Width	420 mm
Max Thickness	8 mm
Min Thickness	0.6/0.2 mm
Knife Dimension	0.7*50*3500 mm